



规格说明: Specifications:
电气特性: Electrical:

- 1. 额定电流: Current Rating
1.5A/contact terminal
- 2. 额定电压: Voltage Rating
30V DC
- 3. 接触电阻: Contact Resistance
30 milliohms MAX
- 4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
- 5. 绝缘电阻: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:

- 1. 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf(MAX)
Unmate force: 1.02kgf(MIN)

原材料: Material:

- 1. 塑壳: Housing:
Hing Temperature Thermoplastics,

电镀: Finish:

- 1. 端子: Contact: Plated Gold in Mating Area
Tin On Solder Tails

- 2. 外壳: Shell:
铜壳四周镀80U”(MIN)镍

Nickel Plating

端子四周镀50U”(MIN)镍,镀金区域镀100—200U”镀金1U”

MANUFACTURE DWG		深圳市金航标电子有限公司		WWW.BDS666.COM	
公差一覽表 TOLERANCE UNLESS OTHERWISE		型号: KH-MICRO-DIP-2P		0755-83044319	
.X±0.20	X±5°	日期 DATE	2016.10.20	单位 UNIT	MM
XX±0.10	X±2°	审核 CHECKED		比例 SCALE	1:1
XXX±0.02	.XX±1°	批准 APPROVE		画法 VIEW	
				制图 DRAWING	
				DWG NO.	
				姓名 NAME	MICRO 2P 90度
				版本 VER	A0
				页数 SHEET	001