



规格说明:Specifications:

电气特性:Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voitage:
500 V AC AT Sea Level
5. 绝缘阻抗: Lnsulation Resistance:
1000MEGA ohms MIN

物理性能:Mechanical:

1. 插拔力: Cnncetor Mate and Unmate Force
Mate force:3.57kgf(MAX)
Unmate force:1.02kgf(MIN)
2. 端子保持力: Terminal Retenion

原材料:Material:

1. 塑胶:Housing:
Hing Temperature Thermaplastics,
PBT White/Black
2. 端子:Contact:Copper Alloy C2680
3. 外壳:Shell: Copper Alloy C2680/SPCC

电镀:Finish:

1. 端子:Contact: Plated Gold in Mating Area;
Tin On Solder Talls
2. 外壳:Shell:
Nickel Plating

RBCOMMENDBD P. C. B PATTBRN LA360 OUT

深圳市金航标电子有限公司

WWW.BDS666.COM

KH-2AF1804ZJ-14.2JB

0755-83044319

UNLESS OTHERWISE SPECIFIED TOLERANCE	
.X	±0.20
.XX	±0.15
.XXX	±0.10
ANG.	±2°

DRAWN	H.Q.huocv
APPROVED	
DATE	2011.03.18

UNIT	MM
SCALE	3/1
SIZE	A4

TITLE	
PART NO.	
DOC. NO.	

REV. A